



# SS-DI Deck Insert Installation

**Congratulations!**

**You have just purchased the finest volleyball system made for outdoor pool use!**

**It is important that you understand how to install the deck inserts in effort to avoid any problems during installation.**

## **IMPORTANT!**

**The screw on the side of the deck insert is a “grounding screw”. Building Codes vary from state to state but typically any metal object within 3 feet of the waters edge will need to be grounded. Should you or your builder decided not to use this stainless steel screw for a ground, we recommend you do the following:**

- 1) Do not remove the screw prior to installation.**
- 2) Back the screw out, only far enough as so that it will not obstruct the support poles. The best way to determine this distance is to back the screw out only far enough so you can not feel the screw from the inside with your finger.**
- 3) This will eliminate any chance of obstruction and will allow the screw to be used as a post, reducing any chance of the insert to twist in its setting.**

## **IMPORTANT!**

**The stainless steel cap has been specially machined to fit your deck inserts.**

- 1) Make sure you keep the cap and threads clean at all times.**
- 2) Use your hands or a dime to screw the cap in place.**
- 3) DO NOT OVER TIGHTEN THE STAINLESS STEEL CAP!**

## **Installation for existing pools: Retrofitting**

- 1) Core drill a 3” to 3-1/2” hole into the area that you wish to install your new deck inserts.**
- 2) When core drilling, keep the new hole a safe distance from the coping to ensure solid footing.**
- 3) Suggested cements: Concrete, Epoxy, liquid nails.**
- 4) Lightly spread play sand over the cement and let deck insert set.**

**Please feel free to contact us if you have questions or if we can be of service.  
The Augustus Group / Coolpoolproducts.com / Customer Service / 972-625-1212  
www.Coolpoolproducts.com**